



STICKA-BLOCK

BITUMEN FLOORING ADHESIVE



STICKA BLOCK IS A RUBBERIZED BITUMEN EMULSION USED FOR FIXING OF 22MM WOODEN FLOORING BLOCKS (NOT FOR USE WITH MINIATURE MOSAIC BLOCK TYPES). BEING WATER BASED IT IS EASY TO USE, DOES NOT GIVE OF HAZARDOUS FUMES, IS NON-FLAMMABLE AS WELL AS ECONOMICAL.



IMPORTANT NOTES

- **No priming is required** but surface areas must be thoroughly cleaned, removing any dust, dirt, grime and any other soiling agents.
- Floors need to be free of any residual moisture; rising damp will also affect the performance of the adhesive. Drying time will be seriously compromised.
- Ensure that blocks being used have not been previously treated with and solvent based preservatives.
- **Do not apply onto wet surfaces.**
- Drying time is approx. 60 minutes but does depends on humidity and air temperature.
- Coverage 2m²/L
- Clean up with warm soapy water when adhesive is wet and solvent once the adhesive has dried.





WATERPROOFING APPLICATION

STEP 1

Preparation

- Surface areas must be thoroughly cleaned, removing any dust, dirt, grime and any soiling agents.
- Surfaces must be dry.

STEP 2

- Using a notched steel trowel evenly apply the adhesive at a rate of 2m²/L.
- Do not under apply.

STEP 3

- Immediately lay wooden blocks into the still wet adhesive. Do not allow adhesive to dry before laying the blocks.
- 48 hours drying time is required for a full cure.



PHYSICAL PROPERTIES

Colour:	Brown-Black
Application:	Notched Steel Trowel
Coverage:	2m ² /L
Drying Time:	48 Hours
Cleaning:	Warm Soapy Water when adhesive is wet and solvent when it is dry
Flammability:	Non-Flammable.





DATA SHEET



HEALTH AND SAFETY

- Avoid contact with skin or eyes.
- Keep out of reach of children.
- If accidentally swallowed, seek medical advice immediately.
- To avoid the risk of spillage, always store and transport containers in a secure upright position.
- Refer to Material Safety Data Sheet for additional information.



STANDARD DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the specifier or user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable. No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond **STT Sales (PTY) LTD** control.

Important Note; It is the responsibility of the user to ensure that the latest TDS is being used for reference. **FLASH HARRY** Data Sheets are available on our website www.flashharry.co.za or Email info@darachem.co.za.

Updated February 2023 (This supersedes all previous publications).

