



MAXI PLAST

PLASTER KEYING AND BONDING LIQUID

- EASY TO MIX WITH CEMENT PRODUCTS, GROUT AND GYPSUM PLASTERS
- INCREASES PLASTER ADHESION, BONDING STRENGTH AND PREVENTS DELAMINATION
- IMPROVED FLEXIBILITY PREVENTS CRACKING AND PAINT FAILURE



DIRECTIONS FOR USE

USAGE PRECAUTIONS

Read all instructions before use. Only apply to dry / damp free surfaces with a moisture content less than 10%. Prime all plaster or concrete surfaces with a suitable Plaster primer*. Only use with fresh moisture free cement / plaster. Maxi Plast is not suitable to be used as a final coat. Do not paint in cold weather below 8°C or if imminent rainfall is expected. In areas affected by heavy dew do not paint after 2pm. Do not apply coating or plaster mix on any contaminated or unsound surface as this will affect the adhesion. Contact our technical help line on 072 396 4980 for assistance prior to painting.

SURFACE PREPARATION

Remove all loose / flaking material. Sand smooth any glossy surfaces. Treat algae or fungi with Fungi Fix* and clean any surface contaminates with Sugar Soap*. Repair cracks, holes or damaged plaster with a suitable plaster mix.

APPLICATION INSTRUCTIONS

Bonding Liquid – Improves surface adhesion and abrasion resistance

Shake product well before use - Apply product with a brush, thoroughly working product into all cracks and holes. This may increase on porous or rough surfaces. Allow 2 – 4 hours drying time. Clean brushes with brush Cleaner*. Product thinning is not recommended.

Plaster Additive – Improves the durability of the plaster, adhesion properties and damp resistance.

Shake product well before use. Thoroughly mix cement and sand. Maxi Plast is ready to use, and no additional water is required. Pour directly into plaster mix as required. Once mixed to a lump free, uniform consistency plaster mix is ready to apply. Clean equipment Brush Cleaner*.



Mixing Guidelines	1 Part of Maxi Plast*
Plaster mix - Cement* 1kg – 4kgs plaster sand	2 – 2.5 litres
Concrete mix - Cement* 1kg - 4kg sand – 3.5kgs stone	1.8 – 2 litres
Tile Adhesive 20kg	8 – 8.5 litres
Tile Grout 1kg	0.55 – 0.65 litres
Gypsum plaster 1kg	1.2 – 1.4 litres

* Guideline quantities results may vary. Adjust mix as required.

*Use product directions displayed on respective products

STORAGE INSTRUCTIONS

Ensure cap is tightly sealed and product stored upright. Secure product when transporting to prevent accidental spillage. Store in a cool place locked away and out of reach of children. Dispose of empty container and do not use for any other purpose. Do not dispose into common waste system. Discard product 18 months after batch date.

SAFETY INSTRUCTIONS



May cause allergic skin reaction.

Read all instructions before use. Replace cap when not in use. Use product in well-ventilated areas. If medical advice is needed, have product packaging at hand. Do not eat or drink when using product. Use personal protection as required. Wear protective gloves. Wear eye protection. Wear a dust mask. Avoid inhalation of dust.

IF IN EYES Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Seek medical attention if symptoms persist.

IF ON SKIN Wash skin with soapy water. Take off immediately all contaminated clothing and wash before reuse. Seek medical attention if symptoms persist.

IF SWALLOWED Rinse mouth with clean water. Do not induce vomiting and seek immediate medical attention. Dispose of contents and packaging in accordance with all local, regional, national and international regulations. National poison centre 0861 555 777



PRODUCT SPECIFICATION

Appearance	White Liquid
Density	1.0 – 1.01 kg/l
pH	8.0 – 9.5