



BITUMEN MASTIC

TROWELABLE WATERPROOFING



BITUMEN MASTIC A THICK BLACK PLASTISIZED SEALER FOR WATERPROOFING ALL IRON, TILED, PITCHED ROOF APPLICATIONS, SKYLIGHTS, ROOF RIDGES, FLASHINGS AND ROOF SCREWS.



DESCRIPTION

Flash Harry Bitumen Mastic is a cost effective, heavy duty, plasticised, solvent based, fibre filled, mastic sealer and repair compound. Recommended for all types of waterproofing such as sheeting laps, valleys, gutters, down pipes, enlarged roof screw holes, cracked tiles, flashings as well as many other details on iron, tiled, concrete, timber and asbestos roof surfaces. Its putty like qualities make it easy to use (no waterproofing membrane needed). It is ideal for patching jobs if rain is imminent.

Stir well before use and use within 6 months of the date indicated on the container.



IMPORTANT NOTES

- All forms of surface contamination must be removed to ensure smooth surface free of any loose material, or any other barrier to adhesion.
- Steel and galvanised steel surfaces must be free of loose paint, grease, grime, oil and rust.
- Bituminous surfaces and torch on membrane surfaces must be free of dust and all loose material.





WATERPROOFING APPLICATION

SURFACE PREPARATION

Surface contamination must be removed to ensure a smooth surface free of any loose material or any other barrier to adhesion. Steel and galvanised steel surfaces must be free of loose paint, grease, grime, oil and rust. Bituminous surfaces and torch on membrane surfaces must be free of dust and all loose material.

- **Flash Harry Bitumen Mastic** may be applied by trowel, putty knife or gloved hand. Coverage is very dependent on the application thickness. In general, 1m²/L per mm film.
- **Flash Harry Bitumen Mastic** is toxic in a wet state. Once dry film has developed it has non tainting properties.
- For maximum U.V. protection it is advised to overcoat **Flash Harry Bitumen Mastic** with **Flash Harry Alu-Coat Silver** once a totally dry film has developed.
- Deviation from the specified instructions will automatically invalidate any claim against non-performance of the product, which in all circumstances is restricted to replacement of product proven defective.
- Technical assistance and applicator training are freely available to all approved users.



PHYSICAL PROPERTIES

Colour:	Black
Application:	Trowel, Scraper or Putty Knife.
Coverage:	Film not less than 2mm and not more than 30mm
Total Solids:	± 75%
Specific Gravity:	± 1.2
Flash Point:	30°C
Cleaning:	White spirits or Mineral turpentine
Flammability:	Flammable when wet; observe all fire ventilation precautions.
Drying Time:	Does not dry but forms a non-tacky film within 12 hours
Dilution:	Do Not Dilute
Pack Size:	500ml, 1L, 5L and 25L





DATA SHEET



HEALTH AND SAFETY

- Avoid contact with skin or eyes.
- Keep out of reach of children.
- If accidentally swallowed, seek medical advice immediately.
- To avoid the risk of spillage, always store and transport containers in a secure upright position.
- Refer to Material Safety Data Sheet for additional information.



STANDARD DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the specifier or user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable. No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond **STT Sales (PTY) LTD** control.

Important Note; It is the responsibility of the user to ensure that the latest TDS is being used for reference. **FLASH HARRY** Data Sheets are available on our website www.flashharry.co.za or Email info@darachem.co.za.

Updated February 2023 (This supersedes all previous publications).

