



SPIRIT OF SALTS

HYDROCHLORIC ACID WASH

- High potency concentrated acid
- Powerful concrete / masonry cleaner
- Etches smooth concrete floors

UN 1789

DIRECTIONS FOR USE

USAGE PRECAUTIONS

Read all instructions before use. Corrosive product, handle with caution and follow all safety instructions. To prevent splash back always add Spirits of Salts to water. Do not use near any alkali or oxidizing materials. Do not use near any metals. Reacts with most metals and forms flammable hydrogen gas. Do not mix with other chemicals. Open cap with caution to prevent any splashing. Do not apply undiluted product as this will damage the surface. Test required dilution ratio before using on a large area.

SURFACE PREPARATION

Sweep and remove any excess loose dirt or excess material on the surface.

APPLICATION INSTRUCTIONS

Light Duty surface contaminants. Dilute 1 part Spirits of Salts with 10 parts clean water. To prevent splash back always add Spirits of Salts to water. Mix with a wooden paddle. Apply diluted product to affected area. Use a hard bristle nylon brush to scrub the affected area. Allow 5 minutes for diluted Spirits of Salts to soak in for improved effectiveness. Thoroughly rinse with clean water. Repeat if necessary.

Heavy duty cleaning. Dilute 1 part Spirits of Salts with 5 parts clean water. To prevent splash back always add Spirits of Salts to water. Mix with a wooden paddle. Apply diluted product to affected area. Use a hard bristle nylon brush or broom to scrub the affected area. Allow 5 minutes for diluted Spirits of Salts to soak in for improved effectiveness. Thoroughly rinse with clean water. Repeat if necessary.

STORAGE INSTRUCTIONS

Ensure lid is tightly sealed and product stored upright. Secure product when transporting to prevent accidental spillage. Store in a cool place, locked up and out of reach of children. Store away from any alkali or oxidizing materials. Attacks many metals producing extremely flammable hydrogen gas. Store away from metals. Dispose of empty container and do not use for any other purpose. Do not dispose into common waste. Discard product 18 months after batch date.



PAINTADETM

SAFETY INSTRUCTIONS



May be corrosive to metals



Causes severe skin burns and eye damage. Causes respiratory irritation.

Read all instructions before use. Use product within well-ventilated areas. Keep out of reach of children. Do not eat, drink, or smoke when using this product. If medical advice is needed, have product packaging at hand. Use personal protective equipment as required. Wear protective gloves. Wear eye protection. Wear a respirator, do not inhale fumes.

IF IN EYES Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Seek medical attention if symptoms persist.

IF INHALED Remove victim to fresh air and keep at rest in a position comfortable for breathing. Seek immediate medical attention.

IF ON SKIN Take off immediately all contaminated clothing and wash before reuse. Wash skin with soapy water. Seek medical attention if symptoms persist.

IF SWALLOWED Wash out mouth with water. Do not induce vomiting and seek immediate medical attention.

Dispose of contents and packaging in accordance with all local, regional, national and international regulations. National poison centre 0861 555 777.



PRODUCT SPECIFICATION

Appearance	Pale Straw
Density	1.1 – 1.15 kg/l
pH	0 – 0.5