



DIY Waterproofing and Damp-proofing solutions.

Carport Cure – Drip Preventor

Discussion

An insulating coating for the underside of sheet metal carports, preventing condensation and subsequent dripping, which results in unsightly white marks and damage to motor vehicle paint work.

Physical Properties

| | |
|---------------|--|
| Colour: | Off White |
| Application: | Brush |
| Coverage: | A single carport (6m x 3m) = 15L A double carport (6m x 6m) = 30L 1L = 1.2m ² Finished two coat application |
| Dry Time: | 60 Minutes |
| Cleaning: | Warm Soapy Water |
| Flammability: | Non – Flammable |

Application

Carport Cure – Drip Preventor is to be applied to the underside of the carport sheeting.

Any existing roof leaks should be sealed using Flash Harry – One Shot on the top side of the carport sheeting.

Priming and preparation – Using a high pressure hose, thoroughly clean the entire under- surface area, removing any dust, dirt, grime and any other soiling agents.

During preparation and application, ensure adequate eye protection (goggles).

If applying to new untreated galvanized iron, the surface should be treated with an acid degreasing primer. Rusted surfaces should be brushed down removing all loose material and treated with a rust converting primer

Avoid applying Carport Cure – Drip Preventor when sheeting is cold (early morning, evening and while it is raining)

Do not apply onto wet surfaces.