



# SQUEEZE N' SEAL

HIGHLY FLEXIBLE WATERPROOF REPAIR GEL



A HIGHLY FLEXIBLE, FIBRE REINFORCED, WATERPROOFING COMPUND FOR A QUICK AND EASY WAY OF SEALING SMALLER WATERPROOFING DETAILS SUCH AS ROOF SCREW BOLTS, CRACKED TILES, ROOF RIDGES, FLASHINGS, OVERLAPS AS WELL AS REPAIRING HAIL DAMAGED AND CRACKED ACRYLIC AND MEMBRANE WATERPROOFING SYSTEMS.



## APPLICATIONS

For use on concrete roof tiles, granular roof tiles, raw plaster and fibre cement surfaces



PITCHED ROOFS -  
TILED, IRON &  
TIMBER



FOR WATERPROOFING  
SMALL  
WATERPROOFING  
DETAILS



PARAPET WALLS,  
CAPPINGS AND  
FLASHINGS



FLASHINGS, LAP  
JOINTS, ROOF SCREW  
HOLES





## IMPORTANT NOTES

- All surfaces should be thoroughly cleaned removing all dust, dirt, grime and any other soiling agents.
- A wire brush should be used to remove all loose or peeling paint until a sound surface is achieved.



## WATERPROOFING APPLICATION

- Shake bottle well.
- Unscrew cap, gently squeeze the bottle applying a generous layer of squeeze and seal.
- Curing time depends on film thickness, humidity and air temperature.
- Do not apply if rain is imminent.
- Do not use to overcoat existing bitumen systems.
- Clean up with water.



## PHYSICAL PROPERTIES

Colour:	White, Grey and Black
Application:	Squeeze On
Coverage:	1L/m <sup>2</sup> (Depending on surface finish)
Total Solids:	± 60%
Specific Gravity:	± 1.2
Viscosity:	Soft viscous paste. 150 Krebs Units at 25°C
Drying Time:	(Between coats) Minimum 30 minutes at 25°C at 65% R.H. (Last Coat) 8 Hours before resistant to rain.
Cleaning:	Water when wet. Ethyl acetate when dry.
Flammability:	Non-Flammable.
Pack Size:	1L





DATA SHEET



## HEALTH AND SAFETY

- Avoid contact with skin or eyes.
- Keep out of reach of children.
- If accidentally swallowed, seek medical advice immediately.
- To avoid the risk of spillage, always store and transport containers in a secure upright position.
- Refer to Material Safety Data Sheet for additional information.



## STANDARD DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the specifier or user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable. No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond **STT Sales (PTY) LTD** control.

Important Note; It is the responsibility of the user to ensure that the latest TDS is being used for reference. **FLASH HARRY** Data Sheets are available on our website [www.flashharry.co.za](http://www.flashharry.co.za) or Email [info@darachem.co.za](mailto:info@darachem.co.za).

Updated February 2023 (This supersedes all previous publications).

