



# FLASH HARRY WONDERFILL

MULTI-PURPOSE CRACK FILLER



A READY MIXED MULTI PURPOSE, INTERIOR AND EXTERIOR, FILLER, WHICH DRIES TO A TOUGH SEMI-FLEXIBLE, SANDABLE AND PAINTABLE SURFACE WITH 101 USES AROUND THE HOME.




## APPLICATIONS

For repairing and filling gaps, cracks, holes on walls, floors, skirtings, ceilings, hollow core doors and windows.



FOR FILLING OF  
CRACKS, GAPS,  
BLEMISHES AND  
HOLES.



FOR FILLING AND  
ADHERING ON  
SKIRTING AND TILES



FOR REPAIRING OF  
WINDOW AND DOOR  
FRAMES AS WELL AS  
REPLACING  
DAMAGED WINDOW  
PUTTT





## IMPORTANT NOTES

- **Wonder-fill** is a multi-purpose interior and exterior filler suitable for repairing and filling gaps, cracks, holes and other blemishes on walls, floors, skirting, ceilings, hollow core doors, window and door frames.
- **Wonder-fill** is an acrylic based filler which has excellent adhesive properties to almost all building substrates (concrete, plaster, brick, paint, timber, Masonite, plaster board and metal). Because of the adhesive properties **Wonder-fill** can successfully be used as a tile adhesive for small repair work as well as replacing damaged window putty.
- For easier sanding of **Wonder-fill** use wet sponge sanding block for quick and easy smooth finish
- **Wonder-fill** can be used in conjunction with a reinforcing membrane on large problematic structural cracks.



## WATERPROOFING APPLICATION

### STEP 1

#### PREPARATION

All surfaces should be free of loose grit, dust, grime and any other soiling agents. Old dusty porous surfaces such as concrete, plaster, brick etc., can be dampened with a small amount of water before application to ensure a stronger bond.

### STEP 2

#### STIR WELL

- Stir **Wonder-fill** before use. **Wonder-fill** can be diluted with water, but it will then be more susceptible to hair line cracking.

### STEP 3

- Apply **Wonder-fill** with a trowel, scraper or putty knife. **Apply in layers not more than 10mm thick, allowing each layer to dry before the next application.** Finishing layers should be smoothed off while wet. If applied to thickly slight hairline cracks may appear during drying, a thin final application of **Wonder-fill** should be applied.

### STEP 4

- After drying the surface may be sanded, dusted off and over coated with chosen paint. **For easier sanding of Wonder-fill use a wet sponge sanding block for a quick and easy smooth finish.**



## PHYSICAL PROPERTIES

Colour:	Off White
Application:	Trowel, Scraper or Putty Knife
Coverage:	1m <sup>2</sup> /L (1mm film thickness)
Specific Gravity:	± 1.85
Viscosity:	Thick paste like consistency
Drying Time:	Depends on film thickness
Cleaning:	Water
Pack Size:	500g, 1L, 5L and 25L



## HEALTH AND SAFETY

- Avoid contact with skin or eyes.
- Keep out of reach of children.
- If accidentally swallowed, seek medical advice immediately.
- To avoid the risk of spillage, always store and transport containers in a secure upright position.
- Refer to Material Safety Data Sheet for additional information.



## STANDARD DISCLAIMER

The recommendations contained herein are given in good faith and meant to guide the specifier or user in accordance with good painting practices. They are gained from our tests and experiences and are believed to be accurate and reliable. No warranty/guarantee is implied by the recommendations contained herein since the conditions of use; application method, substrate and cleanliness of the substrate are beyond **STT Sales (PTY) LTD** control.

Important Note; It is the responsibility of the user to ensure that the latest TDS is being used for reference. **FLASH HARRY** Data Sheets are available on our website [www.flashharry.co.za](http://www.flashharry.co.za) or Email [info@darachem.co.za](mailto:info@darachem.co.za).

Updated February 2023 (This supersedes all previous publications).

